

TVS-472XT-PT-4G	
CPU	Intel® Pentium G5400T 2-core 3.1 GHz Processor
CPU Architecture	64-bit x86
Graphic Processors	Intel® UHD Graphics 610
Floating Point Unit	Yes
Encryption Engine	Yes (AES-NI)
Hardware-accelerated Transcoding	Yes
System Memory	4 GB SODIMM DDR4 (2 x 2 GB)
Maximum Memory	32 GB (2 x 16 GB)
Memory Slot	2 x SO-DIMM DDR4
Flash Memory	5GB (Dual boot OS protection)
Drive Bay	4 x 3.5-inch SATA 6Gb/s, 3Gb/s
Drive Compatibility	3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Hot-swappable	Yes
M.2 SSD Slot	2 x M.2 2280 PCIe Gen3 x2 slots
SSD Cache Acceleration Support	Yes
Gigabit Ethernet Port (RJ45)	2
10 Gigabit/ 5 Gigabit Ethernet Port	1 x 10GBASE-T (10G/5G/2.5G/1G/100M)
Jumbo Frame	Yes
Thunderbolt Port	2 (Thunderbolt™ 3)
PCIe Slot	2 Slot 1: PCIe Gen 3 x16 (CPU) Slot 2: PCIe Gen 3 x4 (PCH)
USB 3.0 port	1
USB 3.1 Gen 2 (10Gbps) Port	2 x Type-C USB 3.1 Gen2 5V/3A 10Gbps 2 x Type-A USB 3.1 Gen2 5V/1A 10Gbps
IR Sensor	Yes (QNAP RM-IR004 & MCE)

HDMI Output	1, HDMI 2.0 (up to 3840 x 2160 @ 60Hz)
Audio Input	1 x 3.5mm microphone input jacks
Audio Output	1 x built-in speaker, 1 x 3.5mm line out jack (for amplifiers or speakers)
Form Factor	Tower
LED Indicators	HDD 1-4, Status, LAN, USB port, M.2 port
LCD Display/ Button	Yes
Buttons	Power, Reset, USB Copy
Dimensions (HxWxD)	188.2 × 199.3 × 279.6 mm
Weight (Net)	5.4 kg
Weight (Gross)	7.01 kg
Operating temperature	0 - 40 °C (32°F - 104°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	250W, 100-240V
Power Consumption: HDD Sleep Mode	24.14 W
Power Consumption: Operating Mode, Typical	37.32 W
Fan	System: 1 x 12cm fan (12V DC) CPU: 2 x 6cm blower fan
Sound Level	21.2 db(A)
System Warning	Voice prompts or Buzzer
Kensington Security Slot	Yes

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Designs and specifications are subject to change without notice.