

3.5 HDD DATA SHEET

The Power of Agility for Creative Pro and SME NAS Enclosures



IronWolf™ Pro is designed for everything business NAS. Get used to tough, ready, and scalable 24x7 performance that can handle multi-drive environments across a wide range of capacities.



Best-Fit Applications

- Commercial and enterprise network-attached storage (NAS)
- 1- to 24-bay network attached storage (NAS)
- Backup, archiving, and disaster recovery
- On-premise private cloud
- Virtual storage



Key Advantages

Optimised for NAS with AgileArray™. AgileArray enables dual-plane balancing and RAID optimisation in multi-bay environments, with the most advanced power management possible.

Actively protect your NAS with IronWolf Health Management focusing on prevention, intervention, and recovery.¹

High performance means no lag time or downtime for users during workload traffic for the NAS. Seagate leads the competition with the highest-performing NAS drive portfolio.²

Seagate® Rescue Data Recovery.³ IronWolf Pro comes with extra peace of mind for any mechanical, accidental, or natural disaster. With a 90% success rate of in-house recovery, Seagate has your back with a 2-year included Rescue Data Recovery plan.

Rotational Vibration (RV) sensors. First in its class of drives to include RV sensors to maintain high performance in multi-drive NAS enclosures.³

Range of capacities up to 16 TB. More capacity options means more choices that will fit within the budget. Seagate provides a scalable solution for any NAS use-case scenario.

Do more in multi-user environments. IronWolf provides a workload rate of 300 TB/year. Multiple users can confidently upload and download data to the NAS server, knowing IronWolf can handle the workload, whether you are a creative professional or a small business.

Designed for always on, always accessible 24x7 performance. Access data on your NAS any time, remotely or on site.

1.2 M hours MTBF, 5-year limited warranty represents an improved total cost of ownership (TCO) over desktop drives with reduced maintenance costs.

¹ Contact your Seagate sales representative for further information.

² Performance may vary depending on user's hardware configuration and operating system.

³ Registration required to activate. Rescue recovery services not available in all countries. Contact your Seagate sales representative for further details.



Specifications	16 TB	14 TB	12 TB	10 TB	8 TB
Capacity	16 TB	14 TB	12 TB	10 TB	8 TB
Standard Model Number ¹	ST16000NE000	ST14000NE0008	ST12000NE0008	ST10000NE0008	ST8000NE001
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
Features					
Drive Bays Supported	Up to 24-bay	Up to 24-bay	Up to 24-bay	Up to 24-bay	Up to 24-bay
Multi-User Technology (TB/yr)	300	300	300	300	300
Rotational Vibration (RV) Sensors	Yes	Yes	Yes	Yes	Yes
Hot-Plug Support ²	Yes	Yes	Yes	Yes	Yes
Cache (MB)	256	256	256	256	256
Reliability/Data Integrity					
Mean Time Between Failures (MTBF, hours)	1,200,000	1,200,000	1,200,000	1,200,000	1,200,000
Reliability Rating @ Full 24x7 Operation (AFR)	0.73%	0.73%	0.73%	0.73%	0.73%
Non-recoverable Read Errors per Bits Read, Max	1 per 10E15	1 per 10E15	1 per 10E15	1 per 10E15	1 per 10E15
Power-On Hours per Year (24x7)	8,760	8,760	8,760	8,760	8,760
Sector Size (Bytes per Logical Sector)	512E	512E	512E	512E	512E
Rescue Services ³	Yes	Yes	Yes	Yes	Yes
Limited Warranty (years)	5	5	5	5	5
Performance					
Spindle Speed (RPM)	7,200	7,200	7,200	7,200	7,200
Interface Access Speed (Gb/s)	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5
Max. Sustained Transfer Rate OD (MB/s)	250MB/s	250MB/s	250MB/s	214MB/s	214MB/s
Average Latency (ms)	4.16	4.16	4.16	4.16	4.16
Interface Ports	Single	Single	Single	Single	Single
Rotational Vibration @ 10-1,500 Hz (rad/s ²)	12.5	12.5	12.5	12.5	12.5
Power Consumption					
Startup Current, Typical (12V, A)	2	2	2	2	2
Idle Power, Average (W)	5	5	5	5	7.06
Average Operating Power (W)	7.6 W	7.6 W	7.8 W	7.8 W	9.2 W
Standby Mode (W)	1	1	1	0.8	1
Sleep Mode (W)	1	1	1	0.8	1
Power Supply Requirements	+12 V and +5 V	+12 V and +5 V	+12 V and +5 V	+12 V and +5 V	+12 V and +5 V
Environmental/Temperature					
Operating (ambient, min °C)	5	5	5	5	5
Operating (drive case, max °C)	60	60	60	60	60
Non-operating (ambient, min °C)	-40	-40	-40	-40	-40
Non-operating (ambient max °C)	70	70	70	70	70
Environmental/Acoustics					
Vibration, Non-operating: 10 Hz to 500 Hz (Grms)	2.27	2.27	2.27	2.27	2.27
Idle (typical) ³	2.8 bels	2.8 bels	2.8 bels	2.8 bels	1.8 bels
Seek (typical)	3.2 bels	3.2 bels	3.2 bels	3bels	2.8 bels
Environmental/Shock					
Shock, Operating 2 ms (Read/Write) (Gs)	50/50 Gs	50/50 Gs	50/50 Gs	70/40 Gs	70/40 Gs
Shock, Non-operating, 1 ms and 2 ms (Gs)	200	200	200	250	250
Physical					
Height (mm/in)	26.11 mm/1.028 in	26.11 mm/1.028 in	26.11 mm/1.028 in	26.11 mm/1.028 in	26.11 mm/1.028 in
Width (mm/in, max)	101.85 mm/4.01 in	101.85 mm/4.01 in	101.85 mm/4.01 in	101.85 mm/4.01 in	101.85 mm/4.01 in
Depth (mm/in, max)	146.99 mm/5.787 in	146.99 mm/5.787 in	146.99 mm/5.787 in	146.99 mm/5.787 in	146.99 mm/5.787 in
Weight (lb/g)	670 g/1.477 lb	670 g/1.477 lb	670 g/1.477 lb	690 g/1.521 lb	722 g/1.59 lb
Carton Unit Quantity	20	20	20	20	20
Cartons per Pallet / Cartons per Layer	40/8	40/8	40/8	40/8	40/8

¹ Seagate recommends validating your configuration with your HBA/RAID controller manufacturer to ensure full capacity capabilities.

² Supports Hot-Plug operation per Serial ATA Revision 2.6 specification.

³ Rescue recovery services not available in all countries. Contact your Seagate sales representative for further details. Register an IronWolf Pro drive to activate your 2-year Rescue plan at seagate.com/register.



Specifications	8 TB	6 TB	6 TB	4 TB	4 TB
Capacity	8 TB	6 TB	6 TB	4 TB	4 TB
Standard Model Number ¹	ST8000NE0021	ST6000NE000	ST6000NE0023	ST4000NE001	ST4000NE0025
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
Features					
Drive Bays Supported	Up to 24-bay	Up to 24-bay	Up to 24-bay	Up to 24-bay	Up to 24-bay
Multi-User Technology (TB/yr)	300	300	300	300	300
Rotational Vibration (RV) Sensors	Yes	Yes	Yes	Yes	Yes
Hot-Plug Support ²	Yes	Yes	Yes	Yes	Yes
Cache (MB)	256	256	256	128	128
Reliability/Data Integrity					
Mean Time Between Failures (MTBF, hours)	1,200,000	1,200,000	1,200,000	1,200,000	1,200,000
Reliability Rating @ Full 24x7 Operation (AFR)	0.73%	0.73%	0.73%	0.73%	0.73%
Non-recoverable Read Errors per Bits Read, Max	1 per 10E15	1 per 10E15	1 per 10E15	1 per 10E15	1 per 10E15
Power-On Hours per Year (24x7)	8,760	8,760	8,760	8,760	8,760
Sector Size (Bytes per Logical Sector)	512E	512E	512E	512E	512E
Rescue Services ³	Yes	Yes	Yes	Yes	Yes
Limited Warranty (years)	5	5	5	5	5
Performance					
Spindle Speed (RPM)	7,200	7,200	7,200	7,200	7,200
Interface Access Speed (Gb/s)	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5
Max. Sustained Transfer Rate OD (MB/s)	214MB/s	214MB/s	214MB/s	214MB/s	214MB/s
Average Latency (ms)	4.16	4.16	4.16	4.16	4.16
Interface Ports	Single	Single	Single	Single	Single
Rotational Vibration @ 10-1,500 Hz (rad/s ²)	12.5	12.5	12.5	12.5	12.5
Power Consumption					
Startup Current, Typical (12V, A)	2	2	2	2	2
Idle Power, Average (W)	8.63	7.06	7.5	5.5	5.45
Average Operating Power (W)	8.78 W	8.1 W	8.1 W	9 W	8.5 W
Standby Mode (W)	0.8	1	0.6	1	0.6
Sleep Mode (W)	0.8	1	0.6	1	0.6
Power Supply Requirements	+12 V and +5 V	+12 V and +5 V	+12 V and +5 V	+12 V and +5 V	+12 V and +5 V
Environmental/Temperature					
Operating (ambient, min °C)	5	5	5	5	5
Operating (drive case, max °C)	60	60	60	60	60
Non-operating (ambient, min °C)	-40	-40	-40	-40	-40
Non-operating (ambient max °C)	70	70	70	70	70
Environmental/Acoustics					
Vibration, Non-operating: 10 Hz to 500 Hz (Grms)	2.27	3	3	3	3
Idle (typical) ³	1.8 bels	2.7 bels	2.7 bels	2.7 bels	2.7 bels
Seek (typical)	2.8 bels	2.7 bels	2.7 bels	2.8 bels	2.8 bels
Environmental/Shock					
Shock, Operating 2 ms (Read/Write) (Gs)	70/40 Gs	70/40 Gs	70/40 Gs	70/40 Gs	70/40 Gs
Shock, Non-operating, 1 ms and 2 ms (Gs)	250	250	250	300	300
Physical					
Height (mm/in)	26.11 mm/1.028 in	26.11 mm/1.028 in	26.11 mm/1.028 in	26.11 mm/1.028 in	26.11 mm/1.028 in
Width (mm/in, max)	101.85 mm/4.01 in	101.85 mm/4.01 in	101.85 mm/4.01 in	101.85 mm/4.01 in	101.85 mm/4.01 in
Depth (mm/in, max)	146.99 mm/5.787 in	146.99 mm/5.787 in	146.99 mm/5.787 in	146.99 mm/5.787 in	146.99 mm/5.787 in
Weight (lb/g)	780 g/1.72 lb	705 g/1.55 lb	705 g/1.55 lb	643 g/1.42 lb	680 g/1.5 lb
Carton Unit Quantity	20	20	20	20	20
Cartons per Pallet / Cartons per Layer	40/8	40/8	40/8	40/8	40/8

¹ Seagate recommends validating your configuration with your HBA/RAID controller manufacturer to ensure full capacity capabilities.

² Supports Hot-Plug operation per Serial ATA Revision 2.6 specification.

³ Rescue recovery services not available in all countries. Contact your Seagate sales representative for further details. Register an IronWolf Pro drive to activate your 2-year Rescue plan at seagate.com/register.



Specifications	2 TB
Capacity	2 TB
Standard Model Number ¹	ST2000NE0025
Interface	SATA 6Gb/s
Features	
Drive Bays Supported	Up to 24-bay
Multi-User Technology (TB/yr)	300
Rotational Vibration (RV) Sensors	Yes
Hot-Plug Support ²	Yes
Cache (MB)	128
Reliability/Data Integrity	
Mean Time Between Failures (MTBF, hours)	1,200,000
Reliability Rating @ Full 24x7 Operation (AFR)	0.73%
Non-recoverable Read Errors per Bits Read, Max	1 per 10E15
Power-On Hours per Year (24x7)	8,760
Sector Size (Bytes per Logical Sector)	512
Rescue Services ³	Yes
Limited Warranty (years)	5
Performance	
Spindle Speed (RPM)	7,200
Interface Access Speed (Gb/s)	6.0, 3.0, 1.5
Max. Sustained Transfer Rate OD (MB/s)	195MB/s
Average Latency (ms)	4.16
Interface Ports	Single
Rotational Vibration @ 10-1,500 Hz (rad/s ²)	12.5
Power Consumption	
Startup Current, Typical (12V, A)	2
Idle Power, Average (W)	4.61
Average Operating Power (W)	6.5 W
Standby Mode (W)	0.8
Sleep Mode (W)	0.8
Power Supply Requirements	+12 V and +5 V
Environmental/Temperature	
Operating (ambient, min °C)	5
Operating (drive case, max °C)	60
Non-operating (ambient, min °C)	-40
Non-operating (ambient max °C)	70
Environmental/Acoustics	
Vibration, Non-operating: 10 Hz to 500 Hz (Grms)	3
Idle (typical) ³	2.2 bels
Seek (typical)	2.6 bels
Environmental/Shock	
Shock, Operating 2 ms (Read/Write) (Gs)	70/40 Gs
Shock, Non-operating, 1 ms and 2 ms (Gs)	300
Physical	
Height (mm/in)	26.11 mm/1.028 in
Width (mm/in, max)	101.85 mm/4.01 in
Depth (mm/in, max)	146.99 mm/5.787 in
Weight (lb/g)	550 g/1.21 lb
Carton Unit Quantity	20
Cartons per Pallet / Cartons per Layer	40/8

¹ Seagate recommends validating your configuration with your HBA/RAID controller manufacturer to ensure full capacity capabilities.

² Supports Hot-Plug operation per Serial ATA Revision 2.6 specification.

³ Rescue recovery services not available in all countries. Contact your Seagate sales representative for further details. Register an IronWolf Pro drive to activate your 2-year Rescue plan at seagate.com/register.

AMERICAS	Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000
ASIA/PACIFIC	Seagate Singapore International Headquarters Pte. Ltd. 90 Woodlands Avenue 7, Singapore 737911, 65-6485-3888
EUROPE, MIDDLE EAST, AND AFRICA	Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00

© 2019 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. AgileArray and IronWolf are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. Seagate reserves the right to change, without notice, product offerings or specifications. DS1914.10-1905GB May 2019